

Strip Light & Mounting Channel

COMPATIBILITY GUIDE



MICRO

HOLDS STRIP UP TO 4MM WIDE



SURFACE MOUNT MICRO
AL-TRK-SM-M




GLO TREAD
AL-TRK-TREAD1-M

NARROW


HOLDS STRIP UP TO 12MM WIDE



SURFACE MOUNT NARROW
AL-TRK-SM-N



RECESSED NARROW
AL-TRK-R *UP TO 11MM WIDE



CORNER NARROW
AL-TRK-CRN-N *UP TO 11MM WIDE



MUD-IN NARROW
AL-TRK-MUD2-N




TILE-IN NARROW
AL-TRK-MUD1-N



IN-FLOOR
AL-TRK-INFLR *UP TO 11MM WIDE

*NOT COMPATIBLE WITH WATERPROOF STRIPS DUE TO COATING



HEAT SINK
AL-TRK-SINK-12



BENDABLE
AL-TRK-BD

*NOT COMPATIBLE WITH STRIPS TALLER THAN 2.54mm

WIDE

HOLDS STRIP ABOVE 12MM WIDE



SURFACE MOUNT WIDE
AL-TRK-SM-W

*CAPABILITY FOR HOLDING MULTIPLE STRIPS PER CHANNEL



RECESSED WIDE
AL-TRK-R-W

*CAPABILITY FOR HOLDING MULTIPLE STRIPS PER CHANNEL



CORNER WIDE
AL-TRK-CRN-W



MUD-IN WIDE
AL-TRK-MUD2-W



IN-FLOOR WIDE
AL-TRK-INFLR-W

*CAPABILITY FOR HOLDING MULTIPLE STRIPS PER CHANNEL



LOW-PROFILE FIXTURE
AL-TRK-LPB

*CAPABILITY FOR HOLDING MULTIPLE STRIPS PER CHANNEL



PENDANT FIXTURE
AL-TRK-LNR

*CAPABILITY FOR HOLDING MULTIPLE STRIPS PER CHANNEL