

# W-SERIES RGBW COLOR CHANGING FLEXIBLE LED STRIP LIGHT

Ultra Bright (18 LEDs/foot)

**MODEL: AL-SL-W-U-RGBW** 







# Description

aspectLED's RGB + White Color Changing Flexible LED strip lights are available in RGB+WW (Warm White 3000K), RGB+NW (Neutral White 4000K) or RGB+DW (Day White 6000K) and are a perfect solution for applications that require a multi-color lighting solution, plus a true white light option. Our Ultra Bright W-Series RGBW flexible LED strip lights are made with wire leads on both ends of each 16.4' reel and can be cut every 6-1/2", allowing you to cut pieces to the length that you need.









## Learn more




	NON-WATERPROOF	WATER RESISTANT	WATERPROOF
Dimensions	1/2" (12mm) wide 1/16" (2mm) thick 16.4' (5M) long	1/2" (12mm) wide 1/8" (3.3mm) thick 16.4' (5M) long	9/16" (14mm) wide 3/16" (4.7mm) thick 16.4' (5M) long
Distance Between LEDs	1/2" (12mm)	1/2" (12mm)	1/2" (12mm)
Cut Length	6-1/2" (165.1mm)	6-1/2" (165.1mm)	6-1/2" (165.1mm)
IP Rating	IP20 Indoor Use Dry Location	IP65 Splash Resistant	IP68 Submersible
Adhesive Backing	Yes / 3M Adhesive	Yes / 3M Adhesive	No
<b>Mounting Method</b>	Adhesive Backing	Adhesive Backing	Mounting Straps or Adhesive Caulk
Input Voltage	24VDC	24VDC	24VDC
Beam Angle	120 Degrees	120 Degrees	120 Degrees
Dimmable	Yes	Yes	Yes
Max Power Consumption	5.5 Watts per foot (18.04 Watts per meter)	5.5 Watts per foot (18.04 Watts per meter)	5.5 Watts per foot (18.04 Watts per meter)
Max Luminous Flux	Up to 450 Lumens per foot (varies by LED color)	Up to 450 Lumens per foot (varies by LED color)	Up to 450 Lumens per foot (varies by LED color)
Color Temperature	Warm White = 3000K Neutral White = 4000K DayWhite = 6000K	Warm White = 3800K Neutral White = 4900K DayWhite = 7000K	Warm White = 3800K Neutral White = 4900K DayWhite = 7000K
LED Type	SMD 5050 RGB and White LED Chips	SMD 5050 RGB and White LED Chips	SMD 5050 RGB and White LED Chips
LED Quantity	18 LEDs per foot (300 per reel)	18 LEDs per foot (300 per reel)	18 LEDs per foot (300 per reel)
Max Run	16.4 feet @ 24VDC	16.4 feet @ 24VDC	16.4 feet @ 24VDC
Weight	0.4 lbs per reel	0.6 lbs per reel	1.2 lbs per reel
Estimated Lifespan	50,000 hours	50,000 hours	50,000 hours
Warranty	1 Year	1 Year	1 Year
Suitable Uses	Dry Location Only	Dry or Damp Locations	Dry, Damp or Wet Locations
Standards/Certifications	UL Listed, RoHS	UL Listed, RoHS	UL Listed, RoHS




## Strip Light Dimensions


#### 24VDC - NON-WATERPROOF



#### **24VDC - WATER RESISTANT**



#### **24VDC - WATERPROOF**



## Accessories

60 Watt LED Power Supply

SKU: AL-PS-N-60

**100 Watt LED Power Supply** 

SKU: AL-PS-N-100

200 Watt LED Power Supply

SKU: AL-PS-N-200

Non-Waterproof 400 Watt Switching LED Power Supply

SKU: AL-PS-N-400



Touch! Wireless RGB+White LED Controller

SKU: AL-CTLR-TOUCH-RGBW

Wireless RGBW Multi-Zone LED Handheld Remote Controller SKU: AL-CTLR-RGBW-4ZRF-RMT

Wireless RGBW Multi-Zone LED Wall Controller

SKU: AL-CTLR-RGBW-3ZRF-WMT







## SKU Builder

MODEL #: **WATERPROOFING: BRIGHTNESS: LED LIGHT COLOR: VOLTAGE:** U **AL-SL** 24 **WN** - Non-Waterproof **U** - Ultra Bright **RGBWW** - RGB + Warm White 24 - 24VDC **WR** - Water Resistant **RGBNW** - RGB + Neutral White **WW**- Waterproof **RGBDW** - RGB + DayWhite

4900 Constellation Drive | Saint Paul, MN 55127