







200 Watt Wide Angle Commercial LED Flood Light (550W Metal Halide Equivalent)

MODEL: AL-FL-S200

DESCRIPTION

aspectLED's flood lights use up to 80% less energy than halogen, metal halide or high pressure sodium lights and put out a much brighter, more even and more aesthetically pleasing light, available in a variety of color temperatures of white.

These lights are perfect for office, retail, and hospitality facilities. Also great for large area lighting, wall washing and accent lighting applications.

Our 200 watt wide angle commercial series LED flood light is the perfect solution for security lighting, flag pole lighting, parking lot lighting, or general exterior illumination. This light puts out approximately the equivalent of a 550W metal halide light!

This flood light is IP65 rated, which means it is suitable for indoor or outdoor use and features an attractively styled body/housing that swivels on an adjustable mounting arm. Looking to use this flood light in your landscaping? Check out our attachable stake base mount!

Accepts a wide voltage range (100-277VAC).

PHYSICAL DIMENSIONS + SPECIFICATIONS

Light Fixture Dimensions	16.7" Long, 12.9" Tall, 7.5" Deep	
LED Driver Input Voltage	100-277VAC	
Beam Angle	120 Degrees	
Max Illumination Distance	200 Feet (76 meters)	
Dimmable	No	
Nominal Power Consumption	200 Watts	
Max Luminous Flux of LED Array	22,000 Lumens (may vary based on LED color choice)	
LED Type	COB LED Chip	
LED Quantity	2 - High Power 100 Watt COB LED	
Fixture Material	Gray Powder Coated Aluminum Body	
Glass	Step-tempered glass	
IP Rating	IP65	
Fixture Weight	22 Pounds	
Estimated Lifespan	Up to 50,000 hours	
Warranty	1 Year	
Suitable Uses	Outdoor, Dry, Damp or Wet Locations	
Standards/Certifications	RoHS	

CERTIFICATIONS





DIMENSIONS



SKU BUILDER

Model Number	LED Color	Housing Color
AL-FL-S200		-
	Warm White (3000K) - WW Cool White (4000K) - CW Natural White (5000K) - NW DayWhite (6000K) - DW	Gray - GR White - WT Black - BK

PHOTOMETRICS

ACCESSORIES Flood Light Landscape Stake Base Mount SKU: AL-FL-STK1 Leviton VPT24-1PZ Programmable Timer Switch

SKU: AL-CTLR-DIMSW-VPT241PZ-WH

Foot-candles at center beam	Lux at center beam	Distance from fixture
202.6	2,180.7	5ft
63.6	684.6	10ft
31.8	342.3	15ft
15.1	162.5	20ft
9.6	103.3	25ft

*Cool white tested. Light output may vary by color temperature.