

MEDIUM IN-GROUND/IN-WALL LED LIGHT

Ultra Bright (9W)

MODEL: AL-IG-M-9



Description

This 9W medium light can be mounted in-ground or in-wall. Perfect for patios, garden walls, decks, docks, gazebos, and many other locations.


These recessed in-ground/in-wall lights are waterproof (with an IP67 rating) and feature a #304 stainless steel trim and aluminum body. These lights come standard with a clear glass trim with stainless steel bezel.

[Learn more](#)



	12VDC	24VDC	120VAC
Light Fixture Dimensions <i>(with mounting sleeve)</i>	4.23" (107mm) diameter 4.6" (117mm) deep	4.23" (107mm) diameter 4.6" (117mm) deep	4.23" (107mm) diameter 4.6" (117mm) deep
Input Voltage	12VDC	24VDC	120VAC
Dimmable	No	No	No
Nominal Power Consumption	9 Watts	9 Watts	9 Watts
Max Luminous Flux of LED Array	520 Lumens <i>(varies by LED color)</i>	520 Lumens <i>(varies by LED color)</i>	520 Lumens <i>(varies by LED color)</i>
LED Type	SMD LED Chips	SMD LED Chips	SMD LED Chips
LED Quantity	3 - High Power 3 Watt LEDs	3 - High Power 3 Watt LEDs	3 - High Power 3 Watt LEDs
Beam Angle	30 Degrees	30 Degrees	30 Degrees
Housing Material	Precision Die-cast Aluminum	Precision Die-cast Aluminum	Precision Die-cast Aluminum
Trim Material	Brushed 304 Stainless Steel <i>(316 available as special order)</i> Clear Glass Lens	Brushed 304 Stainless Steel <i>(316 available as special order)</i> Clear Glass Lens	Brushed 304 Stainless Steel <i>(316 available as special order)</i> Clear Glass Lens
Weight	3 lbs	3 lbs	3 lbs
IP Rating	IP67	IP67	IP67
Lens	Optical, >85% efficient <i>Contact us for availability on frosted lenses.</i>	Optical, >85% efficient <i>Contact us for availability on frosted lenses.</i>	Optical, >85% efficient <i>Contact us for availability on frosted lenses.</i>
Glass	Step-tempered Glass	Step-tempered Glass	Step-tempered Glass
Waterproof Seal	Double silicon gasketed seal	Double silicon gasketed seal	Double silicon gasketed seal
Mounting Sleeve	Precision Die-cast Aluminum Sleeve	Precision Die-cast Aluminum Sleeve	Precision Die-cast Aluminum Sleeve
Suitable Uses	Dry, Damp, or Wet Locations	Dry, Damp, or Wet Locations	Dry, Damp, or Wet Locations
Estimated Lifespan	50,000 hours	50,000 hours	50,000 hours
Warranty	1 Year	1 Year	1 Year
Compatible Power Supplies	Non-Dimmable Power Supplies <i>(Never use with MLV power supplies!)</i>	Non-Dimmable Power Supplies <i>(Never use with MLV power supplies!)</i>	No Power Supply needed
Standards / Certifications	RoHS	RoHS	RoHS

Light Fixture Dimensions



MEDIUM IN-GROUND/IN-WALL LED LIGHT
MODEL: AL-IG-M-9

Accessories

30 Watt LED Power Supply

SKU: AL-PS-W-30



60 Watt LED Power Supply

SKU: AL-PS-W-60



100 Watt LED Power Supply

SKU: AL-PS-W-100



200 Watt LED Power Supply

SKU: AL-PS-W-200



Touch! Wireless RGB

LED Controller*

SKU: AL-CTLR-TOUCH

** for color changing version only*



SKU Builder

MODEL #:

AL-IG-M-9

LED COLOR:

WW - Warm White
CW - Cool White
DW - DayWhite
R - Red
G - Green
B - Blue
Y - Yellow/Amber
RGB - RGB

VOLTAGE

12VDC
24VDC
12VAC
120VAC

WIRE LEAD LENGTH:

2 Feet - [Leave Blank]
25FT - 25 feet
50 FT - 50 feet
100 FT - 100 feet