

# MODERN SQUARE RECESSED INDOOR/OUTDOOR LED IN-WALL STAIR STEP LIGHT

#### **MODEL: AL-IWM-S**







## Description

aspectLED wall lights are bright, energy efficient, offer a modern aesthetic, and offer the industry leading quality and performance aspectLED is known for. Recessed step lights are designed to provide safety and decorative/accent lighting for steps, stairways, risers, walls, and walkways in both indoor and outdoor locations. They are ideal for installation in garden walls, stairways, building entrances, elevator lobbies, pathways, or public parks.

aspectLED in-wall lights can be ordered with an optional mounting sleeve that simplifies installation. This can be used as a placeholder/form for poured in concrete applications, or it can be used as a rough-in for drywall recessed applications, so the fixture itself can be easily wired and installed into the box once everything is ready.

#### Learn more








	24VDC	120VAC			
Exterior Trim/Face Dimensions	6-5/16" wide 6-5/16" tall 1/8" thick	6-5/16" wide 6-5/16" tall 1/8" thick			
Recessed Fixture Dimensions	5-7/8" wide 5-7/8" tall 3-1/4" thick	5-7/8" wide 5-7/8" tall 3-1/4" thick			
LED Driver Input Voltage	24VDC	120VAC			
Dimmable	No	No			
<b>Nominal Power Consumption</b>	1.8 Watts	1.8 Watts			
Max Luminous Flux of LED Array	90 Lumens (may vary based on LED color choice)	90 Lumens (may vary based on LED color choice)			
LED Type	SMD LED Chips	SMD LED Chips			
LED Quantity	24 - High Power LEDs	24 - High Power LEDs			
Beam Angle	60 Degrees	60 Degrees			
Housing Material	Die-cast Aluminum	Die-cast Aluminum			
Trim Material	Die-cast Aluminum	Die-cast Aluminum			
Operating Temperature	-15°C to 50°C (5°F to 122°F)	-15°C to 50°C (5°F to 122°F)			
Weight	2 lbs	2 lbs			
IP Rating	IP65	IP65			
Lens	Optical, >85% efficient	Optical, >85% efficient			
Mounting Sleeve	Included ABS Plastic Sleeve	Included ABS Plastic Sleeve			
Mounting Sleeve Dimensions	6″Tall 6″Wide 4-5/8″Deep	6″Tall 6″Wide 4-5/8″ Deep			
Suitable Uses	Exterior Dry, Damp, or Wet Locations	Exterior Dry, Damp, or Wet Locations			
Average Lifespan	50,000 hours	50,000 hours			
Warranty	1 Year	1 Year			
Standards / Certifications	RoHS, CE RoHS, CE				



# Light Fixture Dimensions



## SKU Builder

MODEL #:	COLOI	R TEMP:	SLEEVE	V	VIRE LEAD LENGTH:		VOLTAGE:
AL-IWM-S	_		_	_		—	
	CW - C DW - D B - Blue G - Gre R - Red	en	N - No SLV - Yes	2 5	PFT - [LEAVE BLANK] PSFT - 25 ft FOFT - 50 ft 100FT - 100 ft		<b>24VDC</b> - 24VDC <b>120VAC</b> - 120VAC