


MICRO SERIES LED LANDSCAPE LIGHT (STAKE MOUNT)

Ultra Bright (3W)

MODEL: AL-LL-MCS-3



Description

This 3W compact landscape light can be stake mounted in the ground. Also available in a surface mounted version for mounting on ground, wall or ceiling surfaces. Perfect for patios, garden walls, decks, docks, gazebos, walkways, and many other locations.

These LED landscape lights are waterproof (with an IP65 rating) and feature an aluminum body. These lights come standard with a clear glass trim.


[Learn more](#)




	12VDC	24VDC	12VAC
Light Fixture Dimensions	1.63" (42mm) diameter 3" (76mm) deep	1.63" (42mm) diameter 3" (76mm) deep	1.63" (42mm) diameter 3" (76mm) deep
Stake Dimensions	6.5" (165mm) tall	6.5" (165mm) tall	6.5" (165mm) tall
Input Voltage	12VDC	24VDC	12VAC
Beam Angle	30 Degrees	30 Degrees	30 Degrees
Dimmable	No	No	No
Nominal Power Consumption	3 Watts	3 Watts	3 Watts
Max Luminous Flux of LED Array	Up to 175 Lumens (varies by LED color)	Up to 175 Lumens (varies by LED color)	Up to 175 Lumens (varies by LED color)
LED Type	SMD LED Chips	SMD LED Chips	SMD LED Chips
LED Quantity	1 - High Power 3 Watt LED	1 - High Power 3 Watt LED	1 - High Power 3 Watt LED
Fixture Material	Precision Machined Aluminum	Precision Machined Aluminum	Precision Machined Aluminum
Lens	Optical, >85% efficient	Optical, >85% efficient	Optical, >85% efficient
Glass	Step-tempered 3mm thickness glass	Step-tempered 3mm thickness glass	Step-tempered 3mm thickness glass
Waterproof Seal	Silicone Seal	Silicone Seal	Silicone Seal
IP Rating	IP65	IP65	IP65
Fixture Weight	1.0 lbs	1.0 lbs	1.0 lbs
Average Lifespan	50,000 hours	50,000 hours	50,000 hours
Warranty	1 Year	1 Year	1 Year
Suitable Uses	Dry, Damp or Wet Locations	Dry, Damp or Wet Locations	Dry, Damp or Wet Locations
Compatible Power Supplies	Non-Dimmable Power Supplies (Never use with MLV power supplies!)	Non-Dimmable Power Supplies (Never use with MLV power supplies!)	Requires Landscape Transformer
Standards / Certifications	RoHS	RoHS	RoHS

Light Fixture Dimensions


ISOMETRIC VIEW




FRONT VIEW




TOP VIEW



SIDE VIEW



BOTTOM VIEW



MICRO SERIES LED LANDSCAPE LIGHT (STAKE MOUNT)
MODEL: AL-LL-MCS-3

Photometrics

Beam Dia at 50% CBCP (inches)	Field Dia at 10% CBCP (inches)	Foot-candles at center beam	Lux at center beam	Distance from fixture
61.4"	84.2"	3.30	35.52	8ft
37.9"	68.5"	5.80	62.43	6ft
28.6"	51.5"	8.20	88.26	5ft
20.0"	45.5"	12.90	138.85	4ft
13.5"	30.0"	24.10	259.41	3ft
10.5"	21.0"	58.00	624.31	2ft

Light measurements may vary by color temperature and many other factors.

Accessories

30 Watt LED Power Supply

SKU: AL-PS-W-30

60 Watt LED Power Supply

SKU: AL-PS-W-60

100 Watt LED Power Supply

SKU: AL-PS-W-100

200 Watt LED Power Supply

SKU: AL-PS-W-200



Touch! Wireless RGB LED Controller

SKU: AL-CTLR-TOUCH



Wireless RGBW Multi-Zone LED Handheld Remote Controller

SKU: AL-CTLR-RGBW-4ZRF-RMT



Wireless RGBW Multi-Zone LED Wall Controller

SKU: AL-CTLR-RGBW-3ZRF-WMT



SKU Builder

MODEL #:

AL-LL-MCS-3

LED LIGHT COLOR:

WW - Warm White
CW - Cool White
DW - DayWhite
R - Red
G - Green
B - Blue
Y - Yellow/Amber
RGB - RGB

VOLTAGE:

12VDC
24VDC
12VAC

WIRE LEAD LENGTH:

2FT - 2 feet
25FT - 25 feet
50FT - 50 feet
100FT - 100 feet

www.aspectLED.com | 888.503.1317 | sales@aspectled.com

For general information purposes only. Specifications, dimensions and construction not guaranteed and are subject to change without notice. Copyright © 2020 ASP Holdings, Inc. All rights reserved.



4900 Constellation Drive | Saint Paul, MN 55127