MODERN SERIES LED LANDSCAPE LIGHT (STAKE MOUNT)

Ultra Bright (15W)

MODEL: AL-LL-MSS-15

Description

This beautiful 15W modern series landscape light can be stake mounted in the ground. Also available in a surface mounted version for mounting on ground, wall or ceiling surfaces. Perfect for architectural landscape lighting, patios, garden walls, decks, docks, gazebos, walkways, and many other locations.

These LED landscape lights are waterproof (with an IP65 rating) and feature an aluminum body. These lights come standard with a clear glass trim.

RoHS Compliant | 1YR WARRANTY

Learn more

4900 Constellation Drive | Saint Paul, MN 55127

Specifications

	12VDC	24VDC	120VAC
Light Fixture Dimensions	4.2" (107mm) diameter 6 (152mm) deep	4.2" (107mm) diameter 6" (152mm) deep	4.2" (107mm) diameter 6" (152mm) deep
Stake Dimensions	10.14" (257mm) in-ground 3.47 (88 mm) above-ground	10.14" (257mm) in-ground 3.47 (88 mm) above-ground	10.14" (257mm) in-ground 3.47 (88 mm) above-ground
Input Voltage	12VDC	24VDC	120VAC
Beam Angle	30 Degrees	30 Degrees	30 Degrees
Dimmable	No	No	No
Nominal Power Consumption	15 Watts	15 Watts	15 Watts
Max Luminous Flux of LED Array	Up to 850 Lumens RGB= Up to 800 Lumens *(varies by LED color)*	Up to 850 Lumens RGB= Up to 800 Lumens *(varies by LED color)*	Up to 850 Lumens RGB= Up to 800 Lumens *(varies by LED color)*
LED Type	SMD LED Chips	SMD LED Chips	SMD LED Chips
LED Quantity	5 - High Power 3 Watt LED	5 - High Power 3 Watt LED	5 - High Power 3 Watt LED
Fixture Material	Precision Machined Aluminum	Precision Machined Aluminum	Precision Machined Aluminum
Lens	Optical, >85% efficient	Optical, >85% efficient	Optical, >85% efficient
Glass	Step-tempered 4mm thickness glass	Step-tempered 4mm thickness glass	Step-tempered 4mm thickness glass
Waterproof Seal	Double Silicone Seal	Double Silicone Seal	Double Silicone Seal
IP Rating	IP65	IP65	IP65
Fixture Weight	3.8 lbs	3.8 lbs	3.8 lbs
Average Lifespan	50,000 hours	50,000 hours	50,000 hours
Warranty	1 Year	1 Year	1 Year
Suitable Uses	Dry, Damp or Wet Locations	Dry, Damp or Wet Locations	Dry, Damp or Wet Locations
Compatible Power Supplies	Non-Dimmable Power Supplies *(Never use with MLV power supplies!)*	Non-Dimmable Power Supplies *(Never use with MLV power supplies!)*	No Power Supply Needed
Standards / Certifications	RoHS	RoHS	RoHS

aspectLED™
A WILSON TOOL COMPANY

4900 Constellation Drive | Saint Paul, MN 55127

Light Fixture Dimensions

ISOMETRIC VIEW

FRONT VIEW

SIDE VIEW

6.05in

Ø4.20in

3.18in

2.95in

3.47in

Ø3.08in

1.93in

10.14in

TOP VIEW

Supply Wire
(Length Specified in SKU)

BOTTOM VIEW

aspectLED
A WILSON TOOL COMPANY

4900 Constellation Drive | Saint Paul, MN 55127

Accessories

30 Watt LED Power Supply
SKU: AL-PS-W-30

60 Watt LED Power Supply
SKU: AL-PS-W-60

100 Watt LED Power Supply
SKU: AL-PS-W-100

200 Watt LED Power Supply
SKU: AL-PS-W-200

Touch! Wireless RGB LED Controller
SKU: AL-CTLR-TOUCH

Wireless RGBW Multi-Zone LED Handheld Remote Controller
SKU: AL-CTLR-RGBW-4ZRF-RMT

Wireless RGBW Multi-Zone LED Wall Controller
SKU: AL-CTLR-RGBW-3ZRF-WMT

SKU Builder

MODEL #:

AL-LL-MSS-15 —

LED LIGHT COLOR:

—

WW - Warm White
CW - Cool White
DW - DayWhite
R - Red
G - Green
B - Blue
Y - Yellow/Amber
RGB - RGB

VOLTAGE:

—

12VDC
24VDC
120VAC

WIRE LEAD LENGTH:

—

2FT - 2 feet
25FT - 25 feet
50FT - 50 feet
100FT - 100 feet

www.aspectLED.com | 888.503.1317 | sales@aspectled.com

aspectLED
A WILSON TOOL COMPANY

4900 Constellation Drive | Saint Paul, MN 55127