

SIGNATURE SERIES LED LANDSCAPE LIGHT (STAKE MOUNT)

Ultra Bright (9W)

MODEL: AL-LL-SSS-9



Description

Our most popular selling landscape light, this 9W signature series landscape light can be stake mounted in ground. Also available in a surface mounted version for mounting on ground, wall or ceiling surfaces. Perfect for architectural landscape lighting, patios, garden walls, decks, docks, gazebos, walkways, and many other locations.

These LED landscape lights are waterproof (with an IP65 rating) and feature an aluminum body. These lights come standard with a clear glass trim.

Learn more




www.aspectLED.com | 888.503.1317 | sales@aspectled.com

For general information purposes only. Specifications, dimensions and construction not guaranteed and are subject to change without notice. Copyright © 2020 ASP Holdings, Inc. All rights reserved.

	12VDC	24VDC	120VAC
Light Fixture Dimensions	3.75" (95mm) diameter 3.38" (86mm) deep	3.75" (95mm) diameter 3.38" (86mm) deep	3.75" (95mm) diameter 3.38" (86mm) deep
Stake Dimensions	6.5" (165mm) long	6.5" (165mm) long	6.5" (165mm) long
Input Voltage	12VDC	24VDC	120VAC
Beam Angle	30 Degrees	30 Degrees	30 Degrees
Dimmable	No	No	No
Nominal Power Consumption	9 Watts	9 Watts	9 Watts
Max Luminous Flux of LED Array	520 Lumens RGB=480 Lumens <i>(varies by LED color)</i>	520 Lumens RGB=480 Lumens <i>(varies by LED color)</i>	520 Lumens RGB=480 Lumens <i>(varies by LED color)</i>
LED Type	SMD LED Chips	SMD LED Chips	SMD LED Chips
LED Quantity	3 - High Power 3 Watt LED	3 - High Power 3 Watt LED	3 - High Power 3 Watt LED
Housing Material	Die-Cast Aluminum with Gray Powder Coating	Die-Cast Aluminum with Gray Powder Coating	Die-Cast Aluminum with Gray Powder Coating
Bezel Trim Material	#304 Stainless Steel	#304 Stainless Steel	#304 Stainless Steel
Lens	Optical, >85% efficient	Optical, >85% efficient	Optical, >85% efficient
Glass	Step-tempered 3mm thickness glass	Step-tempered 3mm thickness glass	Step-tempered 3mm thickness glass
Waterproof Seal	Double Silicone Seal	Double Silicone Seal	Double Silicone Seal
IP Rating	IP65	IP65	IP65
Fixture Weight	1.6 lbs	1.6 lbs	1.6 lbs
Average Lifespan	50,000 hours	50,000 hours	50,000 hours
Warranty	1 Year	1 Year	1 Year
Suitable Uses	Dry, Damp or Wet Locations	Dry, Damp or Wet Locations	Dry, Damp or Wet Locations
Compatible Power Supplies	Non-Dimmable Power Supplies. <i>(Never use with MLV power supplies!)</i>	Non-Dimmable Power Supplies. <i>(Never use with MLV power supplies!)</i>	No Power Supply Needed
Standards / Certifications	RoHS	RoHS	RoHS

Light Fixture Dimensions



SIGNATURE SERIES LED LANDSCAPE LIGHT
MODEL: AL-LL-SSS-9

Photometrics

Beam Dia at 50% CBCP (inches)	Field Dia at 10% CBCP (inches)	Foot-candles at center beam	Lux at center beam	Distance from fixture
33.0"	60.5"	22.8	245.42	8ft
22.0"	40.5"	40.7	438.09	6ft
19.0"	37.0"	57.0	613.54	5ft
17.5"	32.0"	89.6	964.45	4ft
13.0"	22.0"	160.6	1,728.68	3ft
8.5"	16.0"	346.2	3,726.46	2ft

Light measurements may vary by color temperature and many other factors.

Accessories

30 Watt LED Power Supply
 SKU: AL-PS-W-30

60 Watt LED Power Supply
 SKU: AL-PS-W-60

100 Watt LED Power Supply
 SKU: AL-PS-W-100

200 Watt LED Power Supply
 SKU: AL-PS-W-200



Touch! Wireless RGB LED Controller
 SKU: AL-CTLR-TOUCH



Wireless RGBW Multi-Zone LED Handheld Remote Controller
 SKU: AL-CTLR-RGBW-4ZRF-RMT



Wireless RGBW Multi-Zone LED Wall Controller
 SKU: AL-CTLR-RGBW-3ZRF-WMT



SKU Builder

MODEL #:

AL-LL-SSS-9

LED LIGHT COLOR:

- WW** - Warm White
- CW** - Cool White
- DW** - DayWhite
- R** - Red
- G** - Green
- B** - Blue
- Y** - Yellow/Amber
- RGB** - RGB

VOLTAGE:

- 12VDC**
- 24VDC**
- 120VAC**

WIRE LEAD LENGTH:

- 2FT** - 2 feet
- 25FT** - 25 feet
- 50FT** - 50 feet
- 100FT** - 100 feet