

2.75" Round Diffused Low Voltage Puck Light - 3W (25 Watt Equivalent)

MODEL: AL-PK-DF-3W

DESCRIPTION

aspectLED's puck lights are bright, energy efficient, and attractively styled, making them perfect for virtually any residential or commercial application.

Puck lights are trending because of their versatility and ability to fit into small areas and niches to provide light in areas other styles wouldn't be able to fit in – and with an easier install than other recessed or flush mount options. They work great for niches or wall cavities, under cabinets, display cases, or even general room lighting, and are a great alternative to our LED strip lights, or our higher power recessed lights. The low voltage design of these fixtures allows great flexibility with wiring during installation. While traditional incandescent, xenon, or halogen puck lights were known for generating a large amount of heat, LEDs won't get hot to the touch and are efficient and long lasting.

CERTIFICATIONS




PHYSICAL DIMENSIONS + SPECIFICATIONS

Light Fixture Dimensions	2-3/4" diameter, 5/8" tall
LED Driver Input Voltage	12VDC and 24VDC
Dimmable	Yes
Nominal Power Consumption	3 Watts
Max Luminous Flux of LED Array	250 Lumens (may vary based on LED color)
Beam Angle	120 Degrees
LED Type	SMD LED Chips
LED Quantity	24 LEDs
Fixture Material	High performance aluminum alloy
Wire Length	3'
Operating Temperature	-4 degrees Fahrenheit (-20 Celsius) to +122 degrees Fahrenheit (+50 Celsius)
Weight	0.4 lbs
Average Lifespan	50,000 hours
Warranty	1 Year
Suitable Uses	Dry or Damp Locations
Compatible Power Supplies	Dimmable and Non-Dimmable Power Supplies Never use with MLV power supplies!
Standards/Certifications	ETL Listed, RoHS

2.75" Round Diffused Low Voltage Puck Light - 3W (25 Watt Equivalent)

MODEL: AL-PK-DF-3W



SKU BUILDER

Model Number

AL-PK-DF-3W

Voltage

[Empty selection box]

12VDC
24VDC

LED Color

[Empty selection box]

Warm White - WW
Cool White - CW
Day White - DW

Housing Color

[Empty selection box]

Satin Nickel - SN
White - WT
Black - BK

PHOTOMETRICS

*Neutral white tested. Light output may vary by color temperature.

Beam Dia at 50% CBCP (inches)	Field Dia at 10% CBCP (inches)	Foot-candles at center beam	Lux at center beam	Distance from fixture
29.5"	68.5"	13.20	142.08	2ft
44.5"	98.1"	5.50	59.20	3ft
58.0"	136.8"	2.90	31.22	4ft
73.5"	172.1"	1.90	20.45	5ft
92.0"	218.8"	1.40	15.07	6ft
121.3"	284.2"	0.90	9.69	8ft