

5.5" LED RECESSED LIGHT

Flat or Sloped Ceilings - 15 LED (15W)

MODEL: AL-RL-S-55-S



Description

At under 5" tall, our 5.5" round LED recessed light can fit into tight spaces that a traditional recessed can light can't, such as ceilings with ductwork/piping/obstructions, hot-roof ceilings with limited vertical clearance, and tight soffits.

These lights feature an easily adjustable LED face that can be pointed straight downward, making them compatible with sloped ceilings (up to 6/12 pitch). Our slope ceiling recessed lights also make perfect art spotlights or wall accent lights, as they can also be installed in flat ceilings and adjusted to point at walls, artwork, or sculptures.

Learn more




www.aspectLED.com | 888.503.1317 | sales@aspectled.com


For general information purposes only. Specifications, dimensions and construction not guaranteed and are subject to change without notice. Copyright © 2020 ASP Holdings, Inc. All rights reserved.

	24VDC	120VAC
Light Fixture Dimensions	6-5/16" (160mm) diameter 4-1/2" (114mm) tall	6-5/16" (160mm) diameter 4-1/2" (114mm) tall
External LED Driver Dimensions	1-7/16" (36mm) long 1" (25.5mm) wide 15/16" (23mm) tall	6-5/8" (169mm) long 3-3/8 (86mm) wide 1-7/8 (47mm) tall
Cut-Out Hole Size	5-5/8" (143mm) diameter	5-5/8" (143mm) diameter
Sloped Ceilings Angle Range	Up to 6/12 pitch, adjustable to 34°	Up to 6/12 pitch, adjustable to 34°
LED Driver Input Voltage	24VDC	120VAC
Dimmable	Yes	Yes
Nominal Power Consumption	15 Watts	15 Watts
Max Luminous Flux of LED Array	Up to 1640 Lumens (varies by LED color)	Up to 1640 Lumens (varies by LED color)
LED Type	SMD LED Chips	SMD LED Chips
LED Quantity	15 - High Power 1 Watt LEDs	15 - High Power 1 Watt LEDs
Fixture Material	High Performance Aluminum Alloy	High Performance Aluminum Alloy
Weight	1.8 lbs	2.0 lbs
Estimated Lifespan	Up to 50,000 hours	Up to 50,000 hours
Warranty	3 Years	3 Years
IC Rated for Insulation Contact	Yes	Yes
Suitable Uses	Indoors or Outdoors - Dry or Damp Locations	Indoors or Outdoors - Dry or Damp Locations
Compatible Power Supplies	Dimmable Power Supplies, Non-Dimmable Power Supplies (Never use with MLV power supplies!)	No Power Supply Needed (Driver included with light)
Standards/Certifications	RoHS	RoHS


Light Fixture Dimensions



24VDC Driver Dimensions (NOTE: This light includes 3 drivers for 24VDC)



120 VAC Driver Dimensions



5.5" LED RECESSED LIGHT
MODEL: AL-RL-S-55-S

Photometrics

Beam Dia at 50% CBCP (inches)	Field Dia at 10% CBCP (inches)	Foot-candles at center beam	Lux at center beam	Distance from fixture
15° / 60°	15° / 60°	15° / 60°	15° / 60°	
14.6" / 15.6"	24.7" / 27.2"	1824.10 / 818.5	19634.4 / 8810.25	2ft
16.1" / 22.0"	31.6" / 37.5"	798.60 / 364.0	8596.05 / 3918.06	3ft
18.6" / 27.5"	38.3" / 46.7"	422.30 / 207.4	4545.59 / 2232.43	4ft
21.5" / 34.5"	46.0" / 59.5"	277.80 / 134.0	2990.2 / 1442.36	5ft
23.4" / 40.5"	51.0" / 68.3"	193.40 / 94.0	2081.7 / 1011.81	6ft
28.0" / 52.0"	67.5" / 91.1"	107.20 / 53.0	1153.8 / 570.49	8ft

Light measurements may vary by color temperature and many other factors. The beam angle is the angle at which light exits your light fixture. The larger the number, the wider the beam of light that is emitted from the light fixture. This chart shows a 15 and 60 degree beam angle option.

Accessories

Rough-In Plate/Bracket for Round/ Modern Series Recessed LED Lights
 SKU: AL-RL-RP-R55



60 Watt LED Power Supply
 SKU: AL-PS-W-60



Extension Cable for Recessed LED Light
 SKU: AL-RL-EXT



60W Dimmable LED Power Supply
 SKU: AL-PS-W-D-60-24V



SKU Builder

MODEL #:	VOLTAGE:	LED LIGHT COLOR:	TRIM COLOR:	BEAM ANGLE:
AL-RL-S-55-S	24VDC 120VAC	WW - Warm White CW - Cool White DW - DayWhite B - Blue G - Green R - Red Y - Yellow/Amber	SN - Satin Nickel WT - White DB - Dark Bronze BK - Black BS - Brass CH - Chrome	60 - Flood Light (60°) 15 - Spot Light (15°)