



9" ULTRA-THIN SQUARE LED RECESSED LIGHT

18 Watt (125 Watt Equivalent)

MODEL: AL-RL-UTS-9



Description

At under 1" tall, these recessed can lights can fit into tight spaces that a traditional recessed ceiling light cannot, such as ceilings with ductwork/piping/obstructions, hot-roof ceilings with limited vertical clearance, and tight soffits.

This 18 Watt light puts out the equivalent brightness to a incandescent 125 Watt light.

Learn more



www.aspectLED.com | 888.503.1317 | sales@aspectled.com


For general information purposes only. Specifications, dimensions and construction not guaranteed and are subject to change without notice. Copyright © 2020 ASP Holdings, Inc. All rights reserved.




4900 Constellation Drive | Saint Paul, MN 55127

	NON-DIMMABLE	DIMMABLE
Light Fixture Dimensions	8-7/8" (226mm) long 8-7/8" (226mm) wide 7/8" (22mm) tall	8-7/8" (226mm) long 8-7/8" (226mm) wide 7/8" (22mm) tall
Light Trim Dimension	1" (25mm) wide	1" (25mm) wide
Interior Lens Dimensions	6-7/8" (175mm) long 6-7/8" (175mm) wide	6-7/8" (175mm) long 6-7/8" (175mm) wide
External LED Driver Dimensions	6-5/8" (168mm) long 3-3/8" (86mm) wide 1-7/8" (48mm) tall	6-5/8" (168mm) long 3-3/8" (86mm) wide 1-7/8" (48mm) tall
Cut-Out Hole Size	8-1/8" (206mm) long 8-1/8" (206mm) wide	8-1/8" (206mm) long 8-1/8" (206mm) wide
LED Driver Input Voltage	120VAC	120VAC
Dimmable	No	Yes, Compatible with most ELV Dimmers
Nominal Power Consumption	18 Watts	18 Watts
Max Luminous Flux of LED Array	Up to 1510 Lumens <i>(varies by LED color)</i>	Up to 1510 Lumens <i>(varies by LED color)</i>
Beam Angle	120 Degrees	120 Degrees
Equivalency	125 Watts Incandescent/Halogen	125 Watts Incandescent/Halogen
LED Type	High power SMD 2835 LEDs	High power SMD 2835 LEDs
LED Quantity	90 - High Power SMD 2835 LEDs	90 - High Power SMD 2835 LEDs
Housing Color	White	White
Fixture Material	Die Cast Aluminum Housing	Die Cast Aluminum Housing
Weight	2.0 lbs	2.0 lbs
Estimated Lifespan	50,000 hours	50,000 hours
Warranty	3 Years	3 Years
IC Rated for Insulation Contact	Yes	Yes
Suitable Uses	Indoors or Outdoors - Dry or Damp Locations	Indoors or Outdoors - Dry or Damp Locations
Standards/Certifications	UL Listed, cUL Listed, RoHS	UL Listed, cUL Listed, RoHS

Light Fixture Dimensions



External LED Driver Dimensions



9" ULTRA-THIN SQUARE LED RECESSED LIGHT
MODEL: AL-RL-UTS-9

Photometrics

Beam Dia at 50% CBCP (inches)	Field Dia at 10% CBCP (inches)	Foot-candles at center beam	Lux at center beam	Distance from fixture
33.4"	74.1"	87.68	943.72	2ft
44.2"	78.3"	40.85	439.65	3ft
58.1"	147.9"	22.68	244.13	4ft
76.3"	178.6"	15.02	161.62	5ft
93.8"	210.8"	10.50	113.02	6ft
122.00"	286.7"	10.29	110.75	8ft

Light measurements may vary by color temperature and many other factors.

Accessories

Rough-In Plate/Bracket for Ultra-Thin Recessed LED Light
SKU: AL-RL-RP-U9S



Extension Cable for Recessed LED Light
SKU: AL-RL-EXT



Foam Gasket for Ultra-Thin Recessed LED Lights (1 Gasket)
SKU: AL-RL-UT-GSKI-4



Eaton TAL06P1 Dimmer Switch
SKU: AL-CTLR-DIMSW-TAL06P1



Lutron Skylark SELV-300P Dimmer Switch
SKU: AL-CTLR-DIMSW-SELV300P



SKU Builder

AL-RL-UTS-9

DIMMABLE:

D - Dimmable
N - Non-Dimmable

LED LIGHT COLOR:

WW - Warm White
NW - Neutral White
DW - DayWhite